



CAPRICORN 5W-40

Engine Protection Technology Lubricant

Product Description:

CAPRICORN 5W-40 is supreme performance passenger car motor oil formulated from the latest additive technology in fully synthetic base stocks and has been especially developed for all gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

has been designed to exceed the latest Original Equipment Manufacturers' (OEM's) service fill specifications.

CAPRICORN 5W-40 has outstanding thermo-oxidative stability, effectively preventing the formation of sludge and deposits, resulting in a prolonged engine life. It gives improved fuel economy and allows extended oil drain intervals, reducing the costs of ownership. Excellent low temperature fluidity facilitates cold starting of the engine and effectively provides wear protection at low temperatures.

CAPRICORN 5W-40 is recommended for all modern vehicles, including high performance, turbo-charged, multi valve, direct injected gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles. It exceeds the requirements of most modern European, North American and Japanese car manufacturers.

Property:

Name	Test method	Unit	Typical values
Density @ 15°C	ASTM D4052	g/ml	0.85
Kinematic Viscosity @ 40°C	ASTM D445	mm ² /s	76
Kinematic Viscosity @ 100°C	ASTM D445	mm ² /s	13,1
Viscosity Index	ASTM D2270	-	173
Pour Point	ASTM D97	°C	-42
Flash Point (COC)	ASTM D93	°C	202
Sulphated Ash	ASTM D874	wt %	0,78
Product nr: PCMO003	Date Issued: 28/07/2017	Date Superseded:	Revision nr: 01

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. Advice and opinion noted herein are given in good faith and on the basis of the best information available, information is based on past history of the grade only and must not be construed as a guarantee of performance nor any legal liability is accepted by IPC srl or any of its affiliates. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available with your nearest IPC office

Specifications:

API SM/CF; ACEA A3/B3/B4/C3; MB 229.31/229.51; VW 502.00/505.00/505.01; FORD WSS-M2C 917 A; GM DEXOS2; RENAULT RN 0700/RN 0710; BMW LONG LIFE 04; PORSCHE A40;